

IP-CALK10L31CR

QSFP28 100Gbps LR4 10km DDM Receiver

PRODUCT FEATURES

- Supports 103.1Gbps aggregate bit rate
- 4x25Gbps electrical interface
- 4X25Gbps PIN/TIA receiver
- Maximum link length of 10km on Single Mode Fiber
- Hot pluggable QSFP28 footprint
- Duplex LC receptacles
- Single 3.3V power supply
- Maximum power dissipation < 4W
- RoHS-6 compliant and lead-free
- I²C management interface
- 0°C to +70°C case operating temperature



APPLICATIONS

- 100GBASE-LR4 100G Ethernet

COMPLIANCE

- QSFP28 MSA SFF-8665
- IEEE802.3ba 100GBASE-LR4
- ROHS

PRODUCT DESCRIPTION

IP-CALK10L31CR are designed for use in 100 Gigabit Ethernet links on up to 10km reach over SMF. The optical signals are multiplexed to a single –mode fiber through an industry standard LC connector. They are compliant with the QSFP28 MSA and IEEE 802.3bm 100GBASE-LR4 and CAUI-4. Digital diagnostic functions are available via an I2C interface, as specified by the QSFP+ MSA. The optical transceiver is compliant per the RoHS Directive 2011/65/EU.

I. Contact Information

InphilightCo., Ltd

Building 5, Zone E, Guangguxin Center, No.52, Road liufang, Jiangxia district, Wuhan, Hubei, China

If you need more details about datasheet, please contact sales

sales@inphilight.com

Revision History

Version No.	Date	Description
1.0	June 24, 2019	Preliminary datasheet