

PRODUCT FEATURES

- QSFP28 MSA compliant
- 4x25Gb/s electrical interface
- Supports 103.125Gb/s aggregate bit rate
- Up to 30km transmission on single mode fiber
- LC connector
- Commercial case temperature: 0 °C to 70 °C
- Single 3.3V power supply
- Maximum power consumption 4 Watts

APPLICATIONS

- 100G Ethernet
- Data Center Interconnect

COMPLIANCE

- QSFP28 MSA
- SFF-8665
- RoHS 2.0

Ordering information


Part Number	Data Rate(Gb/s)	Media	Wavelength(nm)	Operating distance(km)	Temperature(°C)
IP-CALK30EE1C1	103.125	SMF	T:1304/R:1309	30	0~70
IP-CALK30EE2C1	103.125	SMF	T:1309/R:1304	30	0~70

PRODUCT DESCRIPTION


IP-CALK40EE1(E2)C1 is designed for 30km optical communication applications. The module incorporates one channel optical signal, on 1310nm center wavelength, operating at 50Gbaud data rate. The transmitter path incorporates an EML Driver and a cooled EML together. On the receiver path, the input optical signal is coupled to a Pin photodiode detector. A DSP based gearbox is used to convert 4x25Gbps NRZ signals to 1x50Gbaud PAM4 signal. Also a 4-channel retimer and FEC block are integrated in this DSP. The electrical interface is compliant with IEEE 802.3cd and QSFP28 MSA in the transmitting and receiving directions, and optical interface is compliant to IEEE 802.3cd and 100G Lambda MSA with Duplex LC connector. The module has a maximum power consumption of 4W.

The product is designed with form factor, optical/electrical connection and digital diagnostic interface according to the QSFP28 Multi- Source Agreement (MSA). It has been designed to meet the harshest external operating conditions including temperature, humidity and EMI interference.

1. Block Diagram



2. Pin Diagram



QSFP28 38pin connector (SFF 8665)

3. Pin Descriptions

Pin	Symbol	Name/Description	Notes
1	GND	Ground	1
2	Tx2n	Transmitter Inverted Data Input	
3	Tx2p	Transmitter Non-Inverted Data Input	
4	GND	Ground	1
5	Tx4n	Transmitter Inverted Data Input	
6	Tx4p	Transmitter Non-Inverted Data Input	
7	GND	Ground	1
8	ModSelL	Module Select	
9	ResetL	Module Reset	
10	Vcc Rx	+3.3V Power supply receiver	
11	SCL	2-wire serial interface clock	
12	SDA	2-wire serial interface data	
13	GND	Ground	1
14	Rx3p	Receiver Non-Inverted Data Output	
15	Rx3n	Receiver Inverted Data Output	
16	GND	Ground	1
17	Rx1p	Receiver Non-Inverted Data Output	
18	Rx1n	Receiver Inverted Data Output	
19	GND	Ground	1
20	GND	Ground	1
21	Rx2n	Receiver Inverted Data Output	
22	Rx2p	Receiver Non-Inverted Data Output	
23	GND	Ground	1
24	Rx4n	Receiver Inverted Data Output	
25	Rx4p	Receiver Non-Inverted Data Output	
26	GND	Ground	1
27	ModPrsL	Module Present	
28	IntL	Interrupt	
29	Vcc Tx	+3.3V Power supply transmitter	
30	Vcc1	+3.3V Power supply	
31	LPMode	Low Power Mode	
32	GND	Ground	1
33	Tx3p	Transmitter Non-Inverted Data Input	
34	Tx3n	Transmitter Inverted Data Input	

100G-ER1 30km QSFP28 Optical Transceiver with DDM	IP-CALK30EE1(E2)C1
---	--------------------

35	GND	Ground	1
36	Tx1p	Transmitter Non-Inverted Data Input	
37	Tx1n	Transmitter Inverted Data Input	
38	GND	Ground	1

Note:

1. Circuit ground is internally isolated from chassis ground.

4. Absolute Maximum Ratings

It has to be noted that the operation in excess of any individual absolute maximum ratings might cause permanent damage to this module.

Parameter	Symbol	Min	Typical	Max	Unit	Note
Maximum Supply Voltage	V_{cc}	0		3.6	V	
Storage Temperature	T_s	-40		85	°C	
Relative Humidity	RH	0		85	%	

5. Recommended Operating Conditions

Parameter	Symbol	Min	Typical	Max	Unit	Note
Operating Case Temperature	T_{case}	0		70	°C	
Supply Voltage	V_{cc}	3.135	3.3	3.465	V	
Relative Humidity	RH	5		85	%	
Data Rate (Optical)	DRO		53.125		GBd	
Data Rate (Electrical)	DRE		4*25.78125		Gbps	
Link Distance				30	km	

6. Electrical Characteristics

100G-ER1 Operation (EOL, TOP = 0 ~ 70°C, V_{cc} = 3.135 to 3.465 V)

Parameter	Symbol	Min	Typical	Max	Unit	Note
Power Dissipation				4	W	
Supply Current	I_{cc}			1.15	A	
Transmitter						
Data Rate, each lane			25.78125		Gbps	
Differential Voltage pk-pk	V_{pp}	350			mV	
Input differential impedance	R_{in}		100		Ohm	
Differential Termination Resistance Mismatch				10	%	
Receiver						
Data Rate, each lane			25.78125		Gbps	
Output differential impedance	R_{out}		100		Ohm	
Differential Termination Resistance Mismatch				10	%	
Differential output voltage	$V_{out, pp}$		400		mV	

7. Optical Characteristics

100G-ER1 Operation (EOL, TOP = 0 ~ 70 °C, V_{cc} = 3.135 to 3.465 V)

Parameters	Symbol	Min	Typical	Max	Unit	Notes
Transmitter						
PAM4 Signaling rate	BR	53.125 ± 100 ppm			GBd	
Transmit wavelength	λ_c	1303.54 1308.09		1305.63 1310.19	nm	

100G-ER1 30km QSFP28 Optical Transceiver with DDM	IP-CALK30EE1(E2)C1
---	--------------------

Side-Mode Suppression Ratio	SMSR	30			dB	
Average launch power	P _{out}	0		5.6	dBm	
Optical Modulation Amplitude (OMA)	P _{OMA}			6.4	dBm	
Transmitter and Dispersion Eye Closure for PAM4 (TDECQ)	TDECQ			3.9	dB	
Launch power OFF				-15	dBm	
Extinction Ratio (ER)	ER	5			dB	
Receiver						
PAM4 Signaling rate	BR	53.125 ± 100 ppm			GBd	
Receive wavelength	λ _c	1308.09 1303.54		1310.19 1305.63	nm	
Damage threshold		-2.4			dBm	
Average receive power		-14.7		-3.4	dBm	
Receive power (OMA _{outer})				-2.6	dBm	
Receiver Sensitivity (OMA _{outer})	SEN			-12.5	dBm	1
Stressed Receiver Sensitivity (OMA _{outer})	SRS			-10	dBm	
Receiver reflectance				-26	dB	
LOS Assert				-18	dBm	
LOS De-Assert		-16			dBm	
LOS Hysteresis		0.5			dB	

Notes:


1.Measured with conformance test signal at TP3 for the BER equal to 2.4x10⁻⁴.

8. Digital Diagnostic Monitoring Functions

IP-CALK40EE1(E2)C1 support the I2C-based Diagnostic Monitoring Interface (DMI) defined in document SFF-8665. The host can access real-time performance of transmitter and receiver optical power, temperature, supply voltage and bias current.

Parameter	Accuracy	Unit
Case Temperature	±3	°C
Supply Voltage	±3%	V
Tx Bias Current	±10%	mA
Tx Optical Power	±3	dB
Rx Optical Power	±3	dB

9. Mechanical Specifications



10. Regulatory Compliance

Feature	Reference	Performance
EMC	EN61000-3	Compatible with standards
Electrostatic Discharge (ESD)	IEC/EN 61000-4-2	Compatible with standards
Electromagnetic Interference (EMI)	FCC Part 15 Class B EN 55022 Class B (CISPR 22A)	Compatible with standards
Laser Eye Safety	FDA 21CFR 1040.10, 1040.11 IEC/EN 60825-1, EC/EN 60825-2	Class 1 laser product
Component Recognition	IEC/EN 60950, L 60950	Compatible with standards
RoHS	2011/65/EU	Compatible with standards

11. Contact Information

Wuhan Inphilight Technology Company Limited

NO.4 Building, Bonded Optoelectronics Industrial Park, Wuhan East Lake Comprehensive Bonded Area, NO.777-30 Optics Valley 3rd Road, East Lake Hi-Technology Development Zone, Wuhan, Hubei, China

Email: sales@inphilight.com

12. Revision History

Version No.	Date	Description
1.0	Mar. 4, 2024	Preliminary datasheet
1.1	Jun.30, 2024	Update contact information.